

1 BILL NO. S-91-04-22

2 SPECIAL ORDINANCE NO. S-110-91.

3 AN ORDINANCE approving the awarding of
4 Reference #0231 by the City of Fort
5 Wayne, Indiana, by and through its
6 Department of Purchasing and THE GLIDDEN
7 PAINT COMPANY for the Department of
8 Community & Economic Development.

9 NOW, THEREFORE, BE IT ORDAINED BY THE COMMON COUNCIL OF
10 THE CITY OF FORT WAYNE, INDIANA;

11 SECTION 1. That Reference #0231 between the City of
12 Fort Wayne, by and through its Department of Purchasing and
13 THE GLIDDEN PAINT COMPANY for the Department of Community *
14 Economic Development, respectfully for:


15 the purchase of paint for the 1991
16 Housing & Neighborhood Development
17 Services (HANDS) exterior paint program
18 through the Department of Community &
19 Economic Development;

20 involving a total cost of Twenty-One Thousand and no/100
21 Dollars (\$21,000.00), all as more particularly set forth in
22 said Reference #0231 which is on file in the Office of the
23 Department of Purchasing, and is by reference incorporated
24 herein, made a part hereof, and is hereby in all things
25 ratified, confirmed and approved.

26 SECTION 2. That this Ordinance shall be in full force
27 and effect from and after its passage and any and all
28 necessary approval by the Mayor.

29 
30 Councilmember

31 APPROVED AS TO FORM
32 AND LEGALITY

33 
34 J. Timothy McCaulay, City Attorney

REFERENCE NO.	0231	
DEPARTMENT:	COMMUNITY & ECON DEVELOP	
DATE:	4-18-91	
ITEM/SERVICE:	'91 EXTERIOR PAINT PROGRAM	
PURCHASING INFORMATION		
ADVERTISED BID:	NO	
DATES ADVERTISED:		
OPENING DATE:		
WRITTEN QUOTE:	YES	
DUE DATE:	4-8-91 @ 4:00 PM	
VERBAL QUOTE:		
SINGLE SOURCE:	NO	
NO. OF VENDORS NOTIFIED:	9	
NO. OF VENDORS RECEIVING BID/QUOTE	9	
NO. OF VENDORS RETURNING BID/QUOTE:	7	
NO. OF VENDORS DISQUALIFIED:	0	
NO. OF VENDORS NOT RESPONDING:	2	
DATE SENT TO DEPT FOR RECOMM:	4-18-91	
DATE RECOMM RECEIVED IN PURCH:	4-15-91	
COUNCIL INFORMATION	DATES SENT	EXTENSION DATES
DATE INFO SENT TO LAW DEPT:	4-18-91	
INTRODUCTION DATE:	4-23-91	
DISCUSSION DATE:	5-14-91	
PASSAGE DATE:	5-21-91	
ORDINANCE NO.:		

REFERENCE NO. 0231
EXTERIOR PAINT
C & ED

DESCRIPTION	QTY	TRUE VALUE	PAPE PAINT	REAN STECKBECK	DECORATORS SUPPLY	M A B PAINT	SHERWIN WILLIAMS	GLIDDEN PAINT
PAINT	3000	\$8.25 \$24,750.00	\$6.49 \$19,470.00	\$7.25 \$21,750.00	\$9.23 \$27,690.00	\$7.95 \$23,850.00	\$7.25 \$21,750.00	\$7.00 \$21,000.00
TINT			\$1.00	\$1.00			\$0.75	
COLOR			\$13.95					

REQUEST FOR QUOTATION

City of Fort Wayne

DEPARTMENT OF PURCHASES

NUMBER ONE EAST MAIN STREET ROOM 350

FORT WAYNE, IN 46802

FAX 219-427-1393

PLEASE INDICATE THIS NUMBER
ON ALL CORRESPONDENCEQUOTE
NO.

0231

DATE OF REQUEST

03/28/91

☐ Quotations☒ Sealed
BidsWILL BE RECEIVED AT
THIS OFFICE UNTIL

04/08/91 - 4:00 P.M.

PAGE



TO

GLIDDEN PAINT
5945 N CLINTON ST
FORT WAYNE IN 46825

The Contractor and his sub-contractors, if any, shall not discriminate against any employee or applicant for employment, to be employed in the performance of this contract, with respect to his hire, tenure, conditions or privileges of employment or any matter directly or indirectly related to employment, because of his race, color, religion, national origin or ancestry. Breach of this covenant may be regarded as a material breach of the contract.

REQUEST FOR QUOTATION THIS IS NOT AN ORDER

PLEASE QUOTE BELOW LOWEST PRICES, WHICH **MUST** INCLUDE ALL DELIVERY CHARGES (INCLUDING FREIGHT, PARCEL POST AND EXPRESS) UNLESS OTHERWISE SPECIFIED, FOR PURCHASING MERCHANDISE OR SERVICE DESCRIBED BELOW.

QUOTATIONS WILL BE OPENED IN ACCORDANCE TO RULES AND REGULATIONS ON THE REVERSE SIDE OF THIS SHEET. RESPECTFULLY,

QUANTITY	UNIT	DESCRIPTION	UNIT PRICE	TOTAL
1	LST	EXTERIOR PAINT FOR THE 1991 EXTERIOR PAINT PROGRAM AS PER THE ATTACHED SPECIFICATIONS		
		PRICES TO BE HELD THRU TERM OF AGREEMENT		
		TERM OF AGREEMENT: FROM AWARD DATE TO DEC. 31, 1991		
		FOR INFORMATION CONTACT BARB JONES AT: (319) 427-1140.		
		THIS IS A SEALED QUOTATION - ENVELOPES WILL <u>NOT</u> BE OPENED UNTIL THE DATE AND TIME STATED ABOVE. WE WILL <u>NOT</u> ACCEPT <u>ANY</u> LATE OR FAXED QUOTATIONS.		
		ALWAYS RETURN THIS COPY OF THE QUOTATION TO THE CITY PURCHASING DEPARTMENT WHETHER OR NOT YOU ACCEPT/DECLINE TO QUOTE.		
		TOTAL PRICE <u>\$7.00/gal.</u> DELIVERY <u>yes</u> F.O.B. <u>N/C.</u>		

THIS IS ONLY AN INVITATION TO QUOTE AND NOT AN ORDER. THE ABOVE QUOTES ARE SUBMITTED IN ACCORDANCE WITH THE REGULATIONS ON THE REVERSE SIDE OF THIS SHEET.

SIGNATURE OF BIDDER:

Jerald H. Hopewell

DATE:

4/5/91

VENDOR 4



Paints



City of Fort Wayne
Department of Purchases
One Main Street Room 350
Fort Wayne, In. 46802

The Glidden Company
Paint & Wallcovering Store
7107 West Jefferson Boulevard
Ft. Wayne,
Indiana 46804

Re: 1991 Exterior Paint Program Bid

Dear Sirs,

We the Glidden Company appreciate the opportunity to place a bid for your 1991 Exterior Paint Program. Enclosed you will find the DATA and M.S.D.S. on our Ultra-Hide Exterior Flat House Paint. I have also enclused the price quote and a color chart you requested.

Pigment solids ----- 46%

Vehicle----- 54%

Total----- 100%

If any questions arise concerning this matter please contact myself at 219-436-1854.

Sincerly,

Jerry H. Klopenstein
Jerry Klopenstein
Sales Representative

DATA BANK**Glidden****PROTECTIVE MAINTENANCE COATINGS DATA**

Acrylic Latex House Paint
For Professional Use Only

ULTRA-HIDE^R Flat Latex House Paint No. 9500 Series

For Exterior Wood, Metal, Masonry, Cement-Asbestos, Hardboard,
and Aluminum Siding-

Read Label and Material Safety Data Sheet Prior to Use.

PRODUCT DESCRIPTION

An acrylic latex house paint modified with alkyd for enhanced adhesion. Provides a smooth, uniform flat finish which minimizes surface imperfections. Applies easily, dries quickly, and cleans up with water. Available in a wide range of custom colors.

PRODUCTS AVAILABLE

ULTRA-HIDE Flat Latex House Paint White No. 9500, Pastel Tint Base No. 9518, Intermediate Tint Base No. 9587, and Deep Tint Base No. 9580

TYPICAL USES

Exterior surfaces of residences, schools, churches, hotels, motels, offices, and warehouses. DO NOT USE ON INTERIOR SURFACES.

PRODUCT ADVANTAGES

- * Excellent sheen uniformity and appearance
- * Colors resist fading and chalking
- * Durable and tough
- * Wide color selection
- * Cleans up with water

MATERIAL PREPARATION

DEAMATONE^R Tinting Colorants must be added to tint bases before use in amounts not exceeding those specified in Glidden color literature. Do not tint White No. 9500. Mix thoroughly before use. Thinning is not normally recommended for top-coat applications, but if required to provide desired application properties use



water only not exceeding one pint per gallon of this product. When used for priming, thin as specified below. Do not add oils, driers, or solvents other than water. Do not mix with stains or other paints.

SURFACE PREPARATION

Surfaces must be dry and cleaned free of all contaminants such as dirt, grease, chalk, mildew, and form oils. Remove all peeling or failing paint, then wash the surface thoroughly using high pressure water equipment or a stiff brush or sponge and detergent solution. Rinse with clean water and allow to dry before priming or painting. Remove all mildew by scrubbing with a solution of one tablespoon dry powdered laundry detergent and one quart hypochlorite-type bleach to three quarts warm water, then rinse thoroughly with water. Always wear protective goggles and rubber gloves during scrubbing to avoid eye and skin irritation.

Areas protected from the normal washing action of rain (such as the lower sections of wall areas, under eaves, overhangs, porch ceilings, etc.) are particularly susceptible to the buildup of dirt, mildew, and hard-to-see salt deposits. These deposits, if painted over, can cause loss of adhesion and eventual paint failure. Be especially thorough when cleaning these areas.

WOOD SURFACES

New Wood

Must be cured, dry, and clean. Seal all knots. Prime with GLIDDEN^R Primecoat Oil Base Alkyd No. 3651 or Latex Base No. 3690. Putty all cracks, nail holes, and open joints. NOTE: Cedar and redwood require two coats of Primecoat Oil Base Alkyd No. 3651 to prevent bleeding through of wood dye stains.

Hardboard/Factory Primed

Must be reprimed with GLIDDEN Primecoat Oil Base Alkyd No. 3651. Topcoat with one or two coats of ULTRA-HIDE Flat Latex House Paint. If the hardboard is heavily textured, allow overnight drying between topcoats to avoid possible mudcracking.

Hardboard/Unprimed

Must be primed with GLIDDEN Primecoat Oil Base Alkyd No. 3651, then topcoated with two coats of ULTRA-HIDE Flat Latex House Paint. If the hardboard is heavily textured, allow overnight drying between topcoats to avoid possible mudcracking.

Previously Painted Wood

Surfaces in good condition need only be clean and dry. Remove any cracked, blistered, flaking, or peeling old paint. Prime any exposed wood as well as any heavily eroded areas with GLIDDEN Primecoat Oil Base Alkyd No. 3651. NOTE: Heavily chalked areas should be wire brushed and washed to remove all chalk.

MASONRY SURFACES

(Brick, Stucco, Concrete, Concrete Block, Asbestos-Cement Shingles) -

For new work, apply this product thinned with one pint of clean water per gallon, then follow with an unthinned second coat. For previously painted masonry, clean free of chalk and other contaminants and then apply one or two coats of this product unthinned. Unpainted block should be filled with ULTRA-HIDE Acrylic Latex Block Filler No. 5317 or BLOCKAID™ Masonry Block Filler No. 1971 before application of this product.

METAL SURFACES

Remove loose rust, loose mill scale, and any oily deposits. Prime bare ferrous metal with GLID-GUARD® Alkyd Metal Primer No. 4570 or GLID-GUARD Tank & Structural Primer No. 5205 Red, No. 5206 Gray, or No. 5207 White. Prime bare galvanized metal and aluminum with GLID-GUARD All Purpose Metal Primer No. 5229 or GLID-GUARD Tank & Structural Primer No. 5205 Red, No. 5206 Gray, or No. 5207 White. For previously painted metal (including aluminum siding), clean thoroughly and spot prime any areas of bare metal with the primer specified above for that metal.

APPLICATION

Apply generously using PREMIUM/PRO ULTRA™ brushes or rollers or by spray. Do not brush or roll excessively. Do not apply when surface temperature is below 50° F. or when rain or dew is expected within 12 hours. Two finish coats will provide the best results, particularly when applying colors tinted from Deep Tint Base No. 9380.

SPRAY APPLICATION

Airless Spray

Glidden equipment is specified.

Gun: ASM 400

Pump: GLIDDEN SPRINT™, GLIDDEN 500™, Fluid Tip, 315
GLIDDEN FORMULA ONE™, GLIDDEN 750™, GLIDDEN 750GE™,

Pressure: 1500-1800 psi

COVERAGE

Covers approximately 400 sq. ft. per gallon on smooth surfaces. Porous or textured surfaces may require more paint.

DRYING

Dries to touch in 30-60 minutes, to recoat in 4 hours at 77° F., 50% relative humidity. Allow longer drying times under cooler or more humid conditions.

CLEAN UP

Clean all application immediately after use with warm, soapy water.

MATERIAL SAFETY DATA SHEET

Glidden THE GLIDDEN COMPANY

25 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which The Glidden Company believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The Glidden Company shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.

9500

PAGE 1

SECTION I

PRODUCT IDENTIFICATION 9500 DATE PRINTED 04/04/91
ULTRA-HIDE FLAT LATEX HOUSE PAINT - WHITE

SECTION II-A - HAZARDOUS INGREDIENTS

CHEMICAL NAME	ETHANOL, 2,2'-OXYBIS-	WT.%	1-5
COMMON NAME	DIETHYLENE GLYCOL	SARA	NO
CAS NUMBER	111-46-6	CERCLA	NO
LD50	NOT EST.	OSHA	NO
ARCINOGENICITY LISTED BY	NTP NO	IARC MONOGRAPH	NO
ACGIH TWA	NOT EST.	OSHA TWA	NOT EST.
ACGIH STEL	NOT EST.	OSHA STEL	NOT EST.
OSHA SKIN	CEILING	SUPP REC STD.	NOT EST.
CHEMICAL NAME	KADLIN	WT.%	10-20
COMMON NAME	CLAY	SARA	NO
CAS NUMBER	1332-58-7	CERCLA	NO
LD50	NOT EST.	OSHA	NO
ARCINOGENICITY LISTED BY	NTP NO	IARC MONOGRAPH	NO
ACGIH TWA	10 MG/M3	OSHA TWA	5 MG/M3
ACGIH STEL	NOT EST.	OSHA STEL	NOT EST.
OSHA SKIN	CEILING	SUPP REC STD.	NOT EST.
CHEMICAL NAME	TITANIUM OXIDE	WT.%	10-20
COMMON NAME	TITANIUM DIOXIDE	SARA	NO
CAS NUMBER	13463-67-7	CERCLA	NO
LD50	NOT EST.	OSHA	NO
ARCINOGENICITY LISTED BY	NTP NO	IARC MONOGRAPH	NO
ACGIH TWA	10 MG/M3	OSHA TWA	10 MG/M3
ACGIH STEL	NOT EST.	OSHA STEL	NOT EST.
OSHA SKIN	CEILING	SUPP REC STD.	NOT EST.
CHEMICAL NAME	ZINC OXIDE	WT.%	5-10
COMMON NAME	ZINC OXIDE	SARA	**
CAS NUMBER	1314-13-2	CERCLA	***
LD50	NOT EST.	OSHA	NO
ARCINOGENICITY LISTED BY	NTP NO	IARC MONOGRAPH	NO
ACGIH TWA	10 MG/M3	OSHA TWA	5 MG/M3
ACGIH STEL	NOT EST.	OSHA STEL	NOT EST.
OSHA SKIN	CEILING	SUPP REC STD.	NOT EST.

** THIS CHEMICAL IS SUBJECT TO SARA 313 REPORTING REQUIREMENTS 40 CFR PART 372.

*** THIS CHEMICAL IS A HAZARDOUS SUBSTANCE AS DEFINED BY CERCLA 40 CFR PART 302.4.

SECTION II-B - OTHER INGREDIENTS

CHEMICAL NAME	ACRYLIC COPOLYMER	WT.%	5-10
COMMON NAME	SAME		
CAS NUMBER	TRADE SECRET		
CHEMICAL NAME	WATER	WT.%	40-50
COMMON NAME	WATER		
CAS NUMBER	7732-18-5		

MATERIAL SAFETY DATA SHEET

Glidden

THE GLIDDEN COMPANY

925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which The Glidden Company believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The Glidden Company shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.

9500

PAGE 2

SECTION III - PHYSICAL DATA

VAPOR PRESSURE	NOT DETERMINED	SPECIFIC GRAVITY	1.341
BOILING RANGE	212 - 212 F	WEIGHT PER GALLON	11.17
EVOLATILE BY VOLUME	71.99		
PHYSICAL STATE	LIQUID	COLOR	WHITE
SOLUBILITY IN WATER	NOT DETERMINED	PH	NOT DETERMINED

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	SETA	ABOVE 200 F	LOWER EXPLOSIVE LIMIT	NOT DETERMINED
			UPPER EXPLOSIVE LIMIT	NOT DETERMINED

EXTINGUISHING MEDIA

DRY CHEMICAL OR FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.
MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.

SPECIAL FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.

SECTION V - HEALTH HAZARD DATA

PRIMARY ROUTES OF EXPOSURE

INHALATION
SKIN CONTACT
EYE CONTACT

EFFECTS OF OVEREXPOSURE

INHALATION	IRRITATION OF RESPIRATORY TRACT, LUNGS. PROLONGED INHALATION MAY LEAD TO DIZZINESS AND/OR LIGHTEADEDNESS, HEADACHE, NAUSEA, VOMITING, CENTRAL NERVOUS SYSTEM DEPRESSION, RESPIRATORY PROBLEMS, ANESTHETIC EFFECT OR NARCOSIS.
SKIN CONTACT	IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS, DEFATTING, ABSORPTION THROUGH SKIN.
EYE CONTACT	IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE REDNESS OF EYES.
INGESTION	INGESTION MAY CAUSE FATIGUE, DROWSINESS, NAUSEA, VOMITING, DIARRHEA, SEVERE ABDOMINAL PAIN, CENTRAL NERVOUS SYSTEM DEPRESSION, CENTRAL NERVOUS SYSTEM DAMAGE, LIVER DAMAGE, KIDNEY DAMAGE, BLADDER DAMAGE, PULMONARY EDEMA, UNCONSCIOUSNESS, CYANOSIS, DEATH.

SECTION V - HEALTH HAZARD DATA

SUPPLEMENTAL HEALTH INFORMATION

EXCESSIVE INHALATION OF FUMES MAY LEAD TO METAL FUME FEVER CHARACTERIZED BY A METALLIC TASTE IN MOUTH, EXCESSIVE THIRST, COUGHING, WEAKNESS, FATIGUE, MUSCULAR PAIN, NAUSEA, CHILLS AND FEVER.

A STUDY CONDUCTED BY NTP, USING A CONTINUOUS BREEDING PROTOCOL, DEMONSTRATED THAT DIETHYLENE GLYCOL IN DRINKING WATER AT A CONCENTRATION OF 3.5% EQUIV. TO 6.1 G/KG/DAY RESULTED IN DECREASED FERTILITY AND REPRODUCTIVE PERFORMANCE IN MICE. THESE EFFECTS WERE NOT SEEN IN THE LOWER DOSE LEVELS EVALUATED. SINCE THE EXPOSURE RESULTING FROM INCIDENTAL CONTACT IS LIKELY TO BE LOWER BY SEVERAL DEGREES OF MAGNITUDE AND THE ROUTE OF EXPOSURE USED IN THIS STUDY DOES NOT REFLECT A LIKELY ROUTE FROM OCCUPATIONAL OR CONSUMER USE THE SIGNIFICANCE OF THESE FINDINGS TO HUMANS IS UNCERTAIN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

EYE, SKIN, RESPIRATORY DISORDERS
KIDNEY DISORDERS
LIVER DISORDERS
NERVOUS SYSTEM DISORDERS

SECTION VI - FIRST AID PROCEDURES

INHALATION

REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING.
GET EMERGENCY MEDICAL ATTENTION.
HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY.

SKIN CONTACT

WASH OFF QUICKLY WITH PLENTY OF WATER, THEN SOAP AND WATER. REMOVE CONTAMINATED CLOTHING.
WASH CONTAMINATED CLOTHING BEFORE RE-USE.

EYE CONTACT

FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. OBTAIN EMERGENCY MEDICAL TREATMENT.

INGESTION

IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION VII - REACTIVITY DATA

STABILITY

STABLE

INCOMPATIBILITY

OXIDIZERS, MAGNESIUM.

CONDITIONS TO AVOID

FREEZING.

HAZARDOUS DECOMPOSITION PRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE.

MATERIAL SAFETY DATA SHEET

Glidden THE GLIDDEN COMPANY

925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which The Glidden Company believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The Glidden Company shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.

9500

PAGE 4

SECTION VII - REACTIVITY DATA

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

SECTION VIII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS.

VENTILATE AREA.

SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.

WASTE DISPOSAL

DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

SECTION IX - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE STANDARDS. WHERE RESPIRATORY PROTECTION IS REQUIRED, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS IN ACCORDANCE WITH OSHA STANDARD 29 CFR 1910.134.

VENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES.
IMPERVIOUS GLOVES, FACE SHIELD.

SECTION X - SPECIAL PRECAUTIONS

HANDLING AND STORAGE

STORE BELOW 100°F.
KEEP FROM FREEZING.

OTHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE. IF SANDING IS DONE, WEAR A DUSTMASK TO AVOID BREATHING OF SANDING DUST.

DOT

PAINT, FREEZABLE

Read the first time in full and on motion by Belmont, seconded by Redd, and duly adopted, read the second time title and referred to the Committee on Finance (and the City Plan Commission for recommendation) and Public Hearing to be held after due legal notice, at the Council Conference Room 128, City-County Building, Fort Wayne, Indiana, on _____, 19____, at _____ o'clock _____ M., E.S.

DATED: 4-23-91

Sandra E. Kennedy
SANDRA E. KENNEDY, CITY CLERK

Read the third time in full and on motion by Belmont, seconded by Redd, and duly adopted, placed on its passage. PASSED YES by the following vote:

	AYES	NAYS	ABSTAINED	ABSENT
TOTAL VOTES	<u>9</u>			
BRADBURY	<u>✓</u>			
BURNS	<u>✓</u>			
EDMONDS	<u>✓</u>			
GIAQUINTA	<u>✓</u>			
HENRY	<u>✓</u>			
LONG	<u>✓</u>			
REDD	<u>✓</u>			
SCHMIDT	<u>✓</u>			
TALARICO	<u>✓</u>			

DATED: 5-14-91

Sandra E. Kennedy
SANDRA E. KENNEDY, CITY CLERK

Passed and adopted by the Common Council of the City of Fort Wayne, Indiana, as (ANNEXATION) (APPROPRIATION) (GENERAL)

(SPECIAL)

(ZONING MAP)

ORDINANCE

RESOLUTION NO. D-10-91

on the 14th day of May, 1991,

ATTEST

SEAL

Sandra E. Kennedy
SANDRA E. KENNEDY, CITY CLERK

Samuel J. Talarico
PRESIDING OFFICER

Presented by me to the Mayor of the City of Fort Wayne, Indiana, on the 15th day of May, 1991 at the hour of 11:30 o'clock A. M., E.S.T.

Sandra E. Kennedy
SANDRA E. KENNEDY, CITY CLERK

Approved and signed by me this 15th day of May, 1991, at the hour of 7:00 o'clock P. M., E.S.T.

PAUL HELMKE
PAUL HELMKE, MAYOR

DIGEST SHEET

TITLE OF ORDINANCE: Special

S-91-04-22

DEPARTMENT REQUESTING ORDINANCE: Purchasing

SYNOPSIS OF ORDINANCE: An ordinance approving the award of Ref. No. 0231 for the 1991 exterior paint program through the Department of Community & Economic Development. The cost reflects the lowest and most responsive of seven (7) vendors.

IF NOT LOWEST, WHO WAS AND WHY WERE THEY NOT AWARDED:

EFFECT OF PASSAGE: Housing & Neighborhood Development Services (HANDS) will purchase approximately 3,000 gallons of exterior latex paint with Community Development Block Grant funds. The paint will be distributed to 125 to 150 low & moderate income homeowners who will paint their houses themselves. HANDS staff will inspect the houses after 30 days to make certain they have been painted. The average cost per house is \$140.00. Applicants for the program must sign a statement agreeing to paint their houses in 30 days or to reimburse HANDS for the cost of the paint.

IF REPLACEMENT, WHAT NECESSITATES:

EFFECT OF NON PASSAGE: 125 to 150 low and moderate income homeowners will not be able to paint their houses. Houses with peeling paint have a negative impact on the real estate market in older neighborhoods and can reduce the value of adjacent properties.

PRIOR APPROVAL REQUESTED:

MONIES INVOLVED: Glidden Paint Co. \$21,000.00

PRICE AGREEMENT: Yes

PURCHASE ORDER: No

ACCOUNT INFORMATION: Community & Econ Develop 193-008-PTP7-4293

PRIOR APPROVAL: DATE:
(IF APPLICABLE)

BILL NO. S-91-04-22

REPORT OF THE COMMITTEE ON FINANCE

MARK E. GIAQUINTA, CHAIRMAN
DONALD J. SCHMIDT, VICE CHAIRMAN
BRADBURY, REDD, BURNS

WE, YOUR COMMITTEE ON FINANCE TO WHOM WAS

REFERRED AN (ORDINANCE) ~~(RESOLUTION)~~ approving the awarding
of Reference #0231 by the City of Fort Wayne, Indiana, by
and through its Department of Purchasing and THE GLIDDEN PAINT
COMPANY for the Department of Community & Economic Development

HAVE HAD SAID (ORDINANCE) ~~(RESOLUTION)~~ UNDER CONSIDERATION
AND BEG LEAVE TO REPORT BACK TO THE COMMON COUNCIL THAT SAID
(ORDINANCE) ~~(RESOLUTION)~~

DO PASS

DO NOT PASS

ABSTAIN

NO REC

Mark E. Giaquinta

Donald J. Schmidt

Janet G. Bradbury

Janet G. Bradbury

Janet G. Bradbury

DATED: 5-14-91.

Sandra E. Kennedy
City Clerk